



PRODUCT FEATURES

- HID Replacement for Applications from 175-320 Watts
- Suitable for Total Enclosed Fixture
- IP64 Rating
- 100-277 Voltage Rating
- Can Be Used in Base Up or Base Down Applications
- 50,000 Hour Lifetime Rating
- UL Type B / DLC 4.4 Certified
- 5-Year Limited Warranty

PRODUCT SPECIFICATIONS

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	BASE	BEAM ANGLE
CLC5-36W-5K	36	4860	5000	Ø3.66 x 9.25	E26 / E39	360°
CLC6-36WD	36	5040	5000	Ø3.66 x 9.50	E26 / E(X)39	360°
CLC1-36W-RE *	36	5200	5000	Ø3.35 x 8.62	E26 / E(X)39	360°
CLC5-45W-5K	45	6075	5000	Ø3.66 x 10.43	E26 / E39	360°
CLC6-45WD	45	6300	5000	Ø3.66 x 10.67	E26 / E(X)39	360°
CLC1-45W-RE *	45	6500	5000	Ø3.35 x 9.80	E26 / E(X)39	360°
CLC5-54W-5K	54	7290	5000	Ø3.66 x 10.43	E26 / E39	360°
CLC6-54WD	54	7560	5000	Ø3.66 x 10.67	E26 / E(X)39	360°
CLC1-54W-RE *	54	7800	5000	Ø3.35 x 9.80	E26 / E(X)39	360°
CLC1-63W-RE *	63	9100	5000	Ø3.35 x 10.39	E26 / E(X)39	360°

* Reduced Envelope

