

DESCRIPTION

CATALOG: E450-T-260-SW	STARTING METHOD: Instant Start	INPUT VOLTAGE: 277 V~	OCV: 690 V~	FREQUENCY : 60 Hz
BALLAST TYPE: Energy efficient magnetic	CLASS: P	TYPE: 1 outdoor	LAMP CONNECTION: Series	SOUND RATED: B NO PCB'S

ELECTRICAL CHARACTERISTICS

LAMP TYPE	NUMBER OF LAMPS	LAMP WATTS	MIN. START TEMP. (°F/°C)	INPUT WATTS (Watts)	INPUT CURRENT (Amps)	BALLAST FACTOR	B.E.F.	P.F.	THD %	LAMP CREST FACTOR
F96T12	2	75	50/10	162	0.60	0.93	0.570	0.97	22	1.7
F96T12/ES	2	60	60/16	140	0.56	0.93	0.665	0.90	26	1.7
F84T12	2	70	50/10	148	0.57	0.90	0.605	0.94	22	1.7
F72T12	2	55	0/-18	131	0.52	0.98	0.745	0.91	22	1.7
F64T12	2	52	0/-18	125	0.50	0.97	0.775	0.90	26	1.7
F60T12	2	50	0/-18	115	0.46	0.93	0.805	0.90	22	1.7

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	2.0	11.140	10.5	3.109	11.750	1.7815
	TOL(+/-)	0.010	0.030	0.010	0.050	0.100	0.080
	MM	51	283	267	79	298	45
	TOL(+/-)	0.25	0.80	0.25	1.30	2.50	2.00
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	YELLOW		
INCHES	8	12	12	12	12		
TOL(+/-)	3/8	3/8	3/8	3/8	3/8		
MM	203	305	305	305	305		
TOL(+/-)	10	10	10	10	10		

CARTON CHARACTERISTICS

UNITS/CARTON 6	CARTON/LAYER 12	# OF LAYERS 4	UNITS PALLET 288	PIECE WEIGHT 8 lbs	CARTON WEIGHT 49 lbs	PALLET WEIGHT 2 391 lbs
CARTON PALLET 48	CARTON DIMENSIONS 12" x 12" x 4"		PALLET DIMENSIONS 40" x 48" x 7"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 24"	


MISC.

For Replacement Use Only; Shrink Wrapped Individual Units; Use Cut-Out Lamp Holders.

CARTON LABEL



ELECTRICAL DIAGRAM



PRODUCT LABEL



Certificate No. 006281

1000Bulbs.com®

2140 Merrit Dr.
Garland, TX 75041

CALL TO ORDER
1-800-624-4488

Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.