



## LED LUMINAIRES



### **ProLED® Select Wallpack Series** **Field Selectable Color Temperature** **and Wattage**



The ProLED Select Wallpack Series provides the best value in the Commercial & Industrial Wallpack market to date. The innovative option to select both Wattage and Color Temperature unrivalled in today's market. The WPFS Series products are made of high quality, die-cast aluminum housings and a shatter resistant Borosilicate Glass Lens which offers a traditional, yet robust design. The Traditional Mounting Design with 1/2" knock outs on sides makes installation a breeze.



**Selectable Wattage**

**Selectable Color Temperature**

**Die Cast Aluminum Housing**

**Shatter Resistant Borosilicate Glass Diffuser**

**UL Listed for Wet Locations**

#### **Applications:**

Building Facade  
Industrial Sites  
Commercial Sites  
Safety & Security  
Self Storage Sites

# ProLED® Select Wallpack Series

## Field Selectable Color Temperature and Wattage

Product #: \_\_\_\_\_ Type: \_\_\_\_\_

Project: \_\_\_\_\_ Date: \_\_\_\_\_

Comments: \_\_\_\_\_ Initials: \_\_\_\_\_

### Performance

- Field Selectable Lumen Packages Ranging from 3,900 lumens to 11,650 lumens
- Overall Efficacy <efficacy ranges between 110 - 140 Lm/W
- Field Selectable 3000K, 4000K, and 5000K
- Universal 120-277VAC
- L70 Lumen Maintenance > 50,000 hours at 25C
- CRI >70
- Type IV Distribution

### Controls

120-277V Photocell: The button photocell is designed to control lighting in accordance with ambient light level. It is equipped with quick-response time delay of approximately 3 seconds. The 120-277V operation suits most customer use applications. The product is UL773A listed, as well as CE and RoHS certified.

### Construction

- Field Selectable Wattage and Color Temperature via Dip Switches Inside the Fixture
- Die-Cast Aluminum Housing
- Hinged Door Frame and Captive Screws
- Shatter Resistant Borosilicate Glass Diffuser
- Textured Architectural Bronze Powder-coat Finish
- Silicone Gasketing
- ½" Knock outs on Top & Sides

### Ordering Information

Product Code	Product Number	Product Description	Wattage Options	Equivalent Wattage
WPFS-LW/3CCTU	10352	FIELD SELECTABLE WATTAGE & CCT; LOW WATTAGE: 28W, 40W, 50W, 60W; CCT SELECT: 3000K, 4000K, 5000K; 120-277VAC; BRONZE	28W 40W 60W	3000K 4000K 5000K
WPFS-HW/3CCTU	10353	FIELD SELECTABLE WATTAGE & CCT; HIGH WATTAGE: 80W, 100W; CCT SELECT: 3000K, 4000K, 5000K; 120-277VAC; BRONZE	80W 100W	3000K 4000K 5000K
PC/120-277	10141	BUTTON PHOTOCELL; 120-277VAC		

### Scaled Performance Table

Housing	Nominal Input Power (W)	CRI	Power Factor	3000K			4000K			5000K		
				Actual Input (W)	Lumens	Efficacy	Actual Input (W)	Lumens	Efficacy	Actual Input (W)	Lumens	Efficacy
WPFS-LW/3CCTU	30	80	>0.9	30.51	3910	128	29.81	4133	139	30.16	4048	134
	40	80	>0.9	43.56	5335	122	42.01	5670	135	42.99	5522	128
	60	80	>0.9	65.02	7271	112	62.22	7945	128	64.21	7559	118
WPFS-HW/3CCTU	80	80	>0.9	81.48	9489	116	77.97	10317	132	80.16	10011	125
	100	80	>0.9	99.61	10835	109	95.28	12129	128	98.41	11652	118

# ProLED® Select Wallpack Series

## Field Selectable Color Temperature and Wattage

Product #: \_\_\_\_\_ Type: \_\_\_\_\_

Project: \_\_\_\_\_ Date: \_\_\_\_\_

Comments: \_\_\_\_\_ Initials: \_\_\_\_\_

### Specification Table

Housing	WPFS-LW/3CCTU			WPFS-HW/3CCTU	
Wattage	28	40	60	80	100
Power Factor	<0.9				
L70 Lifetime	>50,000				
Input Voltage	120-277VAC				
Surge Protection	4KV				
Mounting	Traditional - 1/2 " Knockouts on top and sides				
CCT (Selectable)	3000K, 4000K and 5000K				
Warranty	5 Years				
Finish	Bronze				
Ingress Rating	IP65, UL Wet Location				
DLC	DLC Standard				
Lens	Borosilicate Glass				
Housing	Injection Die-Cast Aluminum				
Weight (lbs)	9.59lbs			10.58lbs	
Dimensions	15.55"x10.83"x10.04"			15.55"x10.83"x10.04"	

\*Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to operate past this point at decreased light levels. May not be compatible with all dimming systems, dimming performance may vary by system.  
 Warranty – Commercial / Industrial: This product is warranted for 5 years from the date of purchase.

### Dimensions



